



O.E.M Single Wheels

Available in sizes from 8" Diameter to 17.5" Diameter

Available in bolt patterns 4 on 4", 5 on 4.5", 6 on 6.5", 8 on 6.5"



Dexstar White Spoke Wheels

Available in sizes from 12" Diameter to 16" Diameter

Available in bolt patterns 4 on 4", 5 on 4.5", 6 on 6.5", 8 on 6.5"



Dexstar White Mod Wheels

Available in sizes from 12" Diameter to 16" Diameter

Available in bolt patterns 4 on 4", 5 on 4.5", 6 on 6.5", 8 on 6.5"



O.E.M Dual Wheels

Available in sizes from 16" to 22.5"

Available in bolt patterns 8 on 6.5", 8 on 275mm, 10 on 8.75", 10 on 11.25"



HiSpec Aluminum Star Wheels

Available in sizes from 13" Diameter to 16" Diameter

Available in bolt patterns 5 on 4.5", 6 on 6.5", 8 on 6.5"



HiSpec Aluminum Mod Wheels

Available in sizes from 13" Diameter to 16" Diameter

Available in bolt patterns 5 on 4.5", 6 on 6.5", 8 on 6.5"

Specialty Aluminum Rims - Special Order



Series 06



Series 07



Series 08



Black Mamba



Spoke Black Accent

Hercules Power STR Trailer Radial

| Part # Tire Size & Service Description | Max Rim Width (in) | Max PSI | Max Load (lbs) | Max Load Duals (ls) | Overall Diam (in) | Section Width (in) | Tread Depth (32nds) | Ship Weight (lbs) | Load Range Ply Rating |
|--|-----------------------------|------------|----------------------|------------------------------|-------------------------|--------------------------|---------------------------|-------------------------|--------------------------------|
| HST175-80-R13BC | 5 | 50 | 1360 | 1200 | 24.02 | 6.97 | 9.5 | 18.3 | C / 6 |
| HST205-75-R14BC | 5.5 | 50 | 1760 | 1570 | 26.14 | 7.99 | 10.5 | 22.5 | C / 6 |
| HST205-75-R15BE | 5.5 | 65 | 2150 | 1870 | 27.13 | 7.99 | 10.5 | 25.4 | D / 8 |
| HST225-75-R15BE | 6 | 80 | 2830 | 2470 | 28.31 | 8.78 | 10.5 | 29.8 | E / 10 |
| HST235-80-R16BE | 6.5 | 80 | 3520 | 3080 | 30.79 | 9.25 | 10 | 40.7 | E / 10 |
| HST235/85R16BF | 6.5 | 95 | 3960 | 3520 | 31.73 | 9.25 | 10.5 | 46.3 | F / 12 |



Hercules H-901 Light Truck Radial

| Part # Tire Size & Service Description | Max Rim Width (in) | Max PSI | Max Load (lbs) | Max Load Duals (ls) | Overall Diam (in) | Section Width (in) | Tread Depth (32nds) | Ship Weight (lbs) | Load Range Ply Rating |
|--|-----------------------------|------------|----------------------|------------------------------|-------------------------|--------------------------|---------------------------|-------------------------|--------------------------------|
| HLT23585R16G | 6.5 | 110 | 3750 | 3415 | 31.73 | 9.25 | 14 | 52.5 | G / 14 |



Hercules H-902 Medium Truck Premium All Position

| Part # Tire Size & Service Description | Max Rim Width (in) | Max PSI | Max Load (lbs) | Max Load Duals (ls) | Overall Diam (in) | Section Width (in) | Tread Depth (32nds) | Ship Weight (lbs) | Load Range Ply Rating |
|--|-----------------------------|------------|----------------------|------------------------------|-------------------------|--------------------------|---------------------------|-------------------------|--------------------------------|
| H215/75R175H | 6 | 125 | 4806 | 4542 | 30.2 | 8.3 | 16 | 56.4 | H / 16 |
| H235/75R175H | 6.8 | 125 | 6008 | 5677 | 31.4 | 9.2 | 17 | 63 | H / 16 |
| H255/70R225H | 7.5 | 120 | 5512 | 5071 | 36.6 | 10 | 18 | 93.6 | H / 16 |





Goodyear Marathon ST Trailer Radials

| Tire Size & Service Description | Max Rim Width (in) | Max PSI | Max Load (lbs) | Max Load Duals (ls) | Overall Diam (in) | Section Width (in) | Tread Depth (32nds) | Ship Weight (lbs) | Load Range Ply Rating |
|---------------------------------|--------------------|---------|----------------|---------------------|-------------------|--------------------|---------------------|-------------------|-----------------------|
| ST175-80-R13BC | 5.5 | 50 | 1360 | | 24 | 6.9 | 9 | 19 | C / 6 |
| ST205-75-R14BC | 6.5 | 50 | 1760 | | 26.1 | 7.9 | 10 | 22.6 | C / 6 |
| ST205-75-R15BC | 6.5 | 50 | 1820 | | 27.1 | 7.9 | 9 | 23.9 | C / 6 |
| ST225-75-R15BD | 7 | 65 | 2540 | | 28.3 | 8.7 | 10 | 27.29 | D / 8 |
| ST235-80-R16BE | 7.5 | 80 | 3420 | 3000 | 30.7 | 9.2 | 10 | 40 | E / 10 |



Goodyear G614 RST Light Truck Radial

| Tire Size & Service Description | Max Rim Width (in) | Max PSI | Max Load (lbs) | Max Load Duals (ls) | Overall Diam (in) | Section Width (in) | Tread Depth (32nds) | Ship Weight (lbs) | Load Range Ply Rating |
|---------------------------------|--------------------|---------|----------------|---------------------|-------------------|--------------------|---------------------|-------------------|-----------------------|
| LT23585R16G | 6.5 | 110 | 3750 | 3415 | 30.7 | 9.5 | 12 | 58 | G / 14 |



Goodyear G114 LHT Medium Truck Radial

| Tire Size & Service Description | Max Rim Width (in) | Max PSI | Max Load (lbs) | Max Load Duals (ls) | Overall Diam (in) | Section Width (in) | Tread Depth (32nds) | Ship Weight (lbs) | Load Range Ply Rating |
|---------------------------------|--------------------|---------|----------------|---------------------|-------------------|--------------------|---------------------|-------------------|-----------------------|
| 215-75R-175H | 6.75 | 115 | 4675 | 4410 | 33.7 | 9.4 | 14 | 60 | H / 16 |



| PART# | DESCRIPTION | FINISH | WHEEL PILOT SIZE |
|-----------|---------------------|-----------------|------------------|
| CCP-60C | ABS CENTER CAP ONLY | CHROME | N/A |
| 295EZ | CENTER CAP W/PLUG | CHROME | 2.95" |
| 319EZ | CENTER CAP W/PLUG | CHROME | 3.19" |
| 319EZ-SS | CENTER CAP W/PLUG | STAINLESS STEEL | 3.19" |
| 330EZ | CENTER CAP W/PLUG | CHROME | 3.30" |
| 425EZ | CENTER CAP W/PLUG | CHROME | 4.25" |
| 425EZ-SS | CENTER CAP W/PLUG | STAINLESS STEEL | 4.25" |
| 482EZ | CENTER CAP W/PLUG | CHROME | 4.82" |
| 490EZ-SS | CENTER CAP W/PLUG | STAINLESS STEEL | 4.90" |
| 5125EZ | CENTER CAP W/PLUG | CHROME | 5.125" |
| 5125EZ-SS | CENTER CAP W/PLUG | STAINLESS STEEL | 5.125" |



| PART# | DESCRIPTION | BOLT PATTERN | LUG/WHEEL SIZE |
|-----------|--------------------|--------------|----------------|
| QT545C | HUB COVER CHROME | 5 ON 4.5" | 1/2" |
| QT655C | HUB COVER CHROME | 6 ON 5.5" | 1/2" |
| QT655B | HUB COVER BLACK | 6 ON 5.5" | 1/2" |
| QT765C | HUB COVER CHROME | 8 ON 6.5" | 13/16" |
| QT865C | HUB COVER CHROME | 8 ON 6.5" | 7/8" |
| QT544CLO | WHEEL LINER CHROME | 5 ON 4.5" | 14" WHEEL |
| QT545CLO | WHEEL LINER CHROME | 5 ON 4.5" | 15" WHEEL |
| QT655CLO | WHEEL LINER CHROME | 6 ON 5.5" | 15" WHEEL |
| QT6556CLO | WHEEL LINER CHROME | 6 ON 5.5" | 16" WHEEL |
| QT865CLO | WHEEL LINER CHROME | 8 ON 6.5" | 16" WHEEL |



| PART# | DESCRIPTION | WHEEL SIZE | FINISH |
|-----------|-------------------------|-------------|-----------------|
| GQST50 | SNAP ON SET OF 4 | 15" | STAINLESS STEEL |
| NST06 | DOT BOLT ON SET OF 4 | 16" & 16.5" | STAINLESS STEEL |
| NDT165 | DOT DUAL BOLT ON (4) | 16" & 16.5" | STAINLESS STEEL |
| GDST175 | DOT BOLT ON SET OF 4 | 17.5" | STAINLESS STEEL |
| GQ64 | DUALY TRUCKS SNAP ON(4) | 16" | STAINLESS STEEL |
| PGD168LNT | JAM NUT W/LUG NUT COVER | | |



| PART# | DESCRIPTION |
|---------|--|
| 12CLN | 1/2" CHROME BULGE STYLE WHEEL NUT |
| 12CLN-L | 1/2" CHROME BULGE STYLE WHEEL NUT 1 3/4" LONG |
| 12SSLN | 1/2" STAINLESS STEEL CAPPED ACORN 1 PIECE BULGE |
| 916CLN | 9/16" CHROME ACORN WHEEL NUT |
| X1023R | 1/2" WHEEL NUT RH, 60° CONED |
| 6-53 | 9/16" WHEEL NUT RH, 60° CONED |
| 6-109 | 5/8" WHEEL NUT RH, 90° CONED |
| 95188 | 5/8" FLANGED WHEEL NUT RH |
| 33-52-1 | WHEEL RETAINING RING 9K - 12K, USE WITH 6-109 NUTS |



| PART# | DESCRIPTION |
|-------|--|
| LW433 | 20" CROSS LUG WRENCH (17MM, 3/4", 13/16", 7/8") |
| LW405 | POWER LUG WRENCH W/COMBO SOCKETS 13/16", 7/8" & 17MM, 19MM |

| PART# | DESCRIPTION |
|-------------|-------------------------------------|
| SDS-250/06 | SLIME TIRE SEALANT 8 OZ |
| SDS-500/06 | SLIME TIRE SEALANT 16 OZ |
| SDS-1000/06 | SLIME TIRE SEALANT 32 OZ |
| SDS-1G/02 | SLIME TIRE SEALANT 1 GAL JUG W/PUMP |

